



Model 6000

DEL-AIR's full line of ventilation controls allow you to complete your ventilation system.

Ranging from our simplest Manual Variable Speed control (M100) all the way up to our advanced microprocessorbased control (RAPID), all DEL-AIR controls maintain an optimum environment.

DEL-AIR helps you control your barn environment, all day long!

DEL-AIR controls have easy-to-read display faces with optional digital readouts for dim lighting conditions. Tailor your controls to your needs by opting for model features that include: second stage relay for heating or cooling; combination variable speed/ single speed control; built-in alarm signals for temperature spikes, power failure, or low line voltage; and a variety of programming options.

DEL-AIR Offers a Range of Single Room, Microprocessor-based Controls:

	M100	M3000	M5500	M6000
Description	Manual Variable Speed	Single Stage Variable Speed	3 Stage Room Control w/Alarm	5 Stage Room Control w/Alarm w/Heater Control
Digital Display	No	Yes	Yes	Yes
Operating Voltage	115V	115/230V	115/230V	115/230V
Heater Interlock	No	Yes	Yes	Yes
Total Outputs	1	2	4	6
Variable Speed Outputs	1	1	1	2
Stage 1 Current Rating	6A	10A	10A	8.5A
Stage 2 Current Rating	—	4.4/2.2A @	360W or 6A 115/230V	8.5A
Stage 3 Current Rating	—	—	6A	8.5A
Stage 4 Current Rating	—	—	—	360W or 4.4/2.2A @ 115/230V
Stage 5 Current Rating	—	—	—	360W or 4.4/2.2A @ 115/230V
Alarm Contact Rating	—	—	0.4/0.2A @ 115/230V (2A @ 30VAC)	0.4/0.2A @ 115/230V (2A @ 30VAC)

All controls CSA approved.

