

The Hurricane series has been developed with performance and value in mind. High volume with high efficiency, provides value, at a low cost. Del-Air's reputation for durability comes from well-engineered construction of polyethylene and other corrosion proof materials. Variable speed models are available from 18" to 36", while our 48" fan is on/off, designed for continuous run hot weather applications. Hurricane fans are a perfect fit for efficient, trouble-free use in confinement livestock facilities. Designed with installation, operation and minimal maintenance in mind.

When production relies on healthy livestock ... rely on DEL-AIR!

Product Features

- energy efficient
- 3-year motor warranty
- 18" - 36" variable speed control
- stainless steel hardware
- H48 B.E.S.S. Lab tested
- CSA approved

Hurricane Fan Series

Energy Efficient, High Volume and Low Cost

DEL-AIR Systems is pleased to announce the addition of a new line of exhaust fans to its proven line of ventilation equipment. The Hurricane series is capable of variable speed — all weather performance. The exception is the H48, our continuous run fan, which can move over 27,000 cfm!























Standard Equipment


- polyethylene housing
- inside shutter
- H48 fiberglass orifice
- motor
- outside fingerguard
- automatic belt tensioner (H48 is belt driven, all others direct)
- galvanized steel blade
- powder coated motor mount



Hurricane Fan Specifications

MODEL	AIRFLOW @ 0.00" wg CFM (m ³ /hr)	EFFICIENCY CFM/Watt	ROUGH OPENING		FAN DIAMETER inches (mm)	ATTACHMENT OPTIONS
			Width inches (mm)	Height inches (mm)		
H48*	27096 (46036)	25.1	57 (1448)	57 (1448)	48 (1220)	   
H36	11500 (19538)	20.0	43 (1092)	43 (1092)	36 (915)	   
H24	7000 (11893)	14.5	27 (685)	27 (685)	24 (610)	   
H20	5000 (8495)	12.0	24.5 (622)	24.5 (622)	20 (508)	   
H18	3000 (5097)	10.0	21 (533)	21 (533)	18 (457)	   

* H48 fan tested by B.E.S.S. labs.



DEL-AIR

ISO 9001 CERTIFIED

SYSTEMS

1-800-667-1722

www.del-air.com